

## D3 Wolseley – Mile End

### RAS DIRN Section Page

**Applicability**

---

ARTC Network Wide

---

SMS

---

**Publication Requirement**

---

Internal / External

---

**Primary Source**

---

Previous Section Page version + RACNs

---

**Document Status**

Version #	Date Reviewed	Prepared by	Reviewed by	Endorsed	Approved
1.9	26/02/2021	Manager Procedures Development	Stakeholders	Manager Standards 16/04/2021	GM Technical Standards 16/04/2021

**Amendment Record**

---

**Amendments to the RAS are published at the following link**

---

<https://www.artc.com.au/uploads/RAS-Amendment-Register-Master.xlsx>

---

All changes throughout this document are highlighted in this colour

---

**Disclaimer**

This document has been prepared by ARTC for internal use and may not be relied on by any other party without ARTC's prior written consent. Use of this document shall be subject to the terms of the relevant contract with ARTC.

ARTC and its employees shall have no liability to unauthorised users of the information for any loss, damage, cost or expense incurred or arising by reason of an unauthorised user using or relying upon the information in this document, whether caused by error, negligence, omission or misrepresentation in this document.

**This document is uncontrolled when printed.**


Authorised users of this document should visit ARTC's intranet or extranet (www.artc.com.au) to access the latest version of this document.

## Table of Contents

<b>Table of Contents</b> .....	<b>2</b>
<b>1 Network Diagram</b> .....	<b>3</b>
<b>2 Route Capacity</b> .....	<b>4</b>
<b>3 Special Access Conditions</b> .....	<b>5</b>
3.1 Clearance for Long Bogie Centre, Low Profile Wagons (Mile End to Dynon) .....	5
3.2 Clearances for Short Bogie Centre Grain Hoppers (Adelaide to Wolseley) .....	5
<b>4 Permanent Speed Restrictions</b> .....	<b>6</b>

## 1 Network Diagram

NB: These line maps are indicative only.



## 2 Route Capacity

<b>WOLSELEY – MILE END</b>			
<b>TRAIN TYPE</b>	<b>MAXIMUM SPEED (KM/H)</b>	<b>MAXIMUM AXLE LOAD (TONNES)</b>	
		<b>LOCOS 134T MAXIMUM LOCOMOTIVE WEIGHT</b>	<b>WAGONS</b>
<b>FREIGHT</b>			
EXPRESS FREIGHT	115	22.8*	20
SUPER FREIGHT	110	22.8*	21
REGULAR FREIGHT	80	22.8*	23
STANDARD FREIGHT	80	22.8*	23
<b>PASSENGER</b>		<b>LOCOS</b>	<b>CARRIAGES</b>
LOCO HAULED	115	22.8*	19

Note:

- Route capacity applies where vehicle characteristics and conditions permit.
- \* These posted axles load are to account for the variability in axle loads for some classes of locomotive. The maximum locomotive weight must still be adhered to.

### 3 Special Access Conditions

#### 3.1 Clearance for Long Bogie Centre, Low Profile Wagons (Mile End to Dynon)

The following applies to the conveyance of 53 ft by 10 ft 6 in boxes on long bogie centre, low profile wagons (e.g. RQDW, VQDW, AQDW type – 1020 mm deck height and former 80 ft container wagons):

- The maximum height is 4210 mm and the maximum width is 2500 mm.
- Applies to wagons with bogie centres 17.3 m and an overall length of 24.680 m.
- Wagon(s) must be loaded centrally with 53 ft box and final outline to fit within the above dimensions to compensate for the inswing.

Speed restrictions of 25 km/h apply through tunnels at the following locations:

- Main Line (Mile End to Dynon) Bunbury Street tunnel
- Ambleside (Balhannah)
- Long Gully (Adelaide Hills)
- National Park (Adelaide Hills).

#### 3.2 Clearances for Short Bogie Centre Grain Hoppers (Adelaide to Wolseley)

The following permitted infringements on Railways of Australia rolling stock outline plate D (alternate principal maximum rolling stock outline) are allowable for hopper wagons with bogie centres 10173 mm and an overall length of 12979 mm over headstocks:

- From 1598 mm to 2898 mm high from rail level, the maximum allowable width is:
  - 3050 mm (1525 mm from centre line) at 1598 mm high from rail
  - increasing to 3200 mm (1600 mm from centre line) wide at 2248 mm high from rail
  - decreasing to 3050 mm (1525 mm from centre line) wide at 2898 mm high from rail
- From 3835 mm to 3935 mm high from rail level, the maximum allowable width is 2710 mm (1355 mm from the centre line).

Typical wagons are WW class grain hoppers (as modified to comply with the permitted infringements).

Wagons operating with the above infringement shall be clearly identified and managed by the Operator.

All other provisions of RISSB rolling stock outlines apply.

## 4 Permanent Speed Restrictions

MILE END – WOLSELEY			
LINE SEGMENT	EXCEPTION TO MAXIMUM SPEEDS LOCATION		RESTRICTED SPEED
MILE END	0.000 KM	3.958 KM	50
	3.958 KM	5.190 KM	90
COUNTDOWN DISTANCE MARKER BOARDS ALSO INSTALLED ON APPROACH TO NR4			
GOODWOOD JUNC	5.190 KM	8.310 KM	90
	8.310 KM	8.840 KM	60
	8.840 KM	11.240 KM	90
	11.240 KM	12.830 KM	70
	12.830 KM	19.750 KM	60
BELAIR	19.750 KM	21.800 KM	55
	21.800 KM	23.020 KM	75
MT LOFTY	23.020 KM	31.340 KM	50
	31.340 KM	39.650 KM	55
	39.650 KM	42.685 KM	50
	42.700 KM	45.200 KM	60
BALHANNAH	45.200 KM	45.700 KM	50
	45.700 KM	49.460 KM	75
	49.460 KM	52.400 KM	55
	52.400 KM	52.630 KM	50
	52.630 KM	54.570 KM	55
	54.570 KM	59.330 KM	65
PETWOOD	59.330 KM	59.770 KM	60
	59.770 KM	62.000 KM	65
	62.000 KM	62.600 KM	55
	62.600 KM	66.500 KM	60
	66.500 KM	72.010 KM	75
	72.010 KM	72.860 KM	100
MONARTO SOUTH	72.860 KM	75.810 KM	105
	75.810 KM	77.110 KM	70 (115 TO MELBOURNE)
	85.080 KM	89.060 KM	105 (115 TO ADELAIDE)
	89.060 KM	91.630 KM	60
	91.630 KM	91.800 KM	75

MILE END – WOLSELEY			
	91.800 KM	96.210 KM	100
MURRAY BRIDGE	96.210 KM	96.700 KM	60
	96.700 KM	98.100 KM	50
	98.100 KM	99.820 KM	70 (115 TO MELBOURNE)
TAILEM BEND			
COOMANDOOK	152.869		
COONALPYN			
TINTINARA	212.104		
COOMBE			
KEITH	246.866		
WIRREGA			
BORDERTOWN	294.070	294.640	75
	294.640	295.610	100
	300.800	301.440	100
WOLSELEY			

## 5 Special Speed Restrictions

MILE END – WOLSELEY		
LOCATION	MAXIMUM SPEED	
	WHEN RUNNING FROM LINES DIVERGING FROM THE STRAIGHT TRACK (KM/H)	WHEN RUNNING ON THE STRAIGHT TRACK (KM/H)
ALL DUAL GAUGE TURNOUTS	20	LINE SPEED FOR TYPE OF TRAIN