

OPERATIONAL NOTICE

Notice No. **24-003**

Notice Type:	Route Access Condition Notice				
Subject Title:	Trial Operation of Aurizon's WDP Coal Train Tahmoor to SSFL				
Operator(s):	Aurizon				
Effective From:	06/03/2024		Effective To:	06/03/2025	
Reference Documents:					
Route Access Standard:		RAS General Information			

General Details / Operating Condition:

A waiver to the conditions of the Route Access Standard permits the operation of a wired distributed power (WDP) train with QHAH / QHBH wagons between Tahmoor and the ARTC – Sydney Trains Interfaces at Sefton Park Junction, Flemington Junction and Meeks Rd Junction.

Conditions of trial shall be as follows:

- 1. Locomotive classes approved for inclusion in this trial include; 6000, 6020, ACD & CF
- 2. Wired distribution power consist in the following configurations:
 - 3 × Approved Locomotives + up to 46 × QHAH / QHBH Coal Wagons, or
 - 2 × Approved Locomotives + up to 44 × QHAH / QHBH Coal Wagons
- 3. QHAH / QHBH hoppers are permitted to be loaded up to a maximum of **98.9 tonne gross (due to bridge loading criteria)**
- 4. The total trailing load shall not exceed 4,550 tonnes.
- 5. The loaded WDP consist shall be in one of the following configurations:
 - 2 × Approved locomotives 46 × QHAH / QHBH wagons 1 × Approved locomotive
 - 1 × Approved locomotive 46 × QHAH / QHBH wagons 2 × Approved locomotives
 - 1 × Approved locomotive 44 × QHAH / QHBH wagons 1 × Approved locomotives
- 6. The empty WDP consist shall be in one of the following configurations:
 - $2 \times \text{Approved locomotive} 46 \times \text{QHAH} / \text{QHBH wagons} 1 \times \text{Approved locomotive}$ (with one offline locomotive in the consist)
 - 1 × Approved locomotive 46 × QHAH / QHBH wagons 2 × Approved locomotives (with one locomotive offline in the consist)
 - 1 × Approved locomotive 44 × QHAH / QHBH wagons 1 × Approved locomotive
- 7. The train shall be operating in ECP and WDP mode.
- 8. WDP operation shall be in operated synchronous mode only.
- 9. There shall be no mixing of empty (or part loaded) and loaded wagons in the consist.
- 10. The use of dynamic braking should be limited whenever there are dead or offline locomotives in the consist (for example in the empty train).
- 11. Train recovery shall be as per Aurizon's Illawarra Coal Operation Plan

Approval: Approved by: Carolyne Southern – Operations Standards Manager Date: 05/03/2024